



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: FABRIC PRESPRAY
CU65

SECTION 1: PRODUCT INFORMATION

Distributed By: Bridgepoint Systems, 4282 W 590 W, Salt Lake City, Utah 84123
Company Phone Number: 801-261-1282
Emergency Phone Number: 1-800-535-5053 (Infotrac)
Date Prepared: 4/1/08 c

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)
Fire: 0 Health: 1 Reactivity: 0

SECTION 2: INGREDIENTS

<u>PRINCIPLE HAZARDOUS INGREDIENTS :</u>	<u>OSHA PEL</u>
Surfactant mixture	N/E
Diethylene Glycol buytl ether (Cas # 112-34-5)	N/E

SECTION 3: PHYSICAL DATA

Boiling Point (°F).....349°F	Specific Gravity(H ₂ O=1).....1.016
Vapor Pressure (mmHg.).....N/D	Percent Volatile by Volume... N/D
Vapor Density (AIR=1)..... N/D	PH (1% Solution).....8
Solubility in Water..... N/D	

Appearance & Odor.....Clear liquid with mint scent

SECTION 4: FIRE, EXPLOSION & REACTIVITY DATA

Flash Point: >212°F

Extinguishing Media: Product is not flammable. Use water, carbon dioxide, dry powder or other media appropriate for materials actually involved in fire.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and full protective clothing

Unusual Fire and Explosion Hazards: None

Stability: Stable

Chemical Incompatibility: Avoid strong oxidizing or alkaline agents

Hazardous Decomposition or Byproducts: During a fire, smoke may contain the original material in addition to unidentified toxic and/or irritating compounds. Hazardous combustion products may include and are not limited to carbon dioxide and carbon monoxide

Hazardous Polymerization: Will not occur

Conditions to Avoid: Only those listed under Chemical Incompatibility

